



# TECHNICAL DATA SHEET

Type no.		514 00/AUX 14	
Article no.		025514000101	
Standards		DIN EN 50342, DIN IEC 60095-2	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		12 Ah (K20)	
Cold start current		200 A (EN)	
Dimensions and weights			
Box	AUX14		
Length max.	150mm		
Width max.	88mm		
Box height max.	145mm		
Total height max.	145mm		
Battery weight	Ca. 4,0 kg (+/- 5 %)	Symbolpicture	
Electrolyte density	Approx. 1,32 kg/l		
Electrolyte	Diluted sulphuric acid		
Items/pallet	195		
Pallet ID	Euro palett		
Items per layer	65		
Features			
Base hold-down	B00		
Layout	1		
Terminal	S10		
Separator	AGM separator		
Degassing	Battery with central degassing		
Flame arrester	Available		
Maintenance <sup>1)</sup>			
Water consumption	< 1g/Ah		
Refill water			
Self-discharge	Approx. 3 % per month		
Charging current	Approx. 1/20 of the rated capacity		
Charging voltage <sup>2)</sup>	max. 14.8 V		

<sup>1)</sup> All the listed values relate to room temperature +25° C

<sup>2)</sup> Recommendation with an external, voltage-regulated charge

Document DBTBAT00254 prepared on 2013-09-19 ; Rights relating to changes and errors retained.  
original