



TECHNICAL DATA SHEET

| | |
|----------------------------------|---|
| Type no. | 530 34 |
| Article no. | 010530340101 |
| Standards | DIN EN 50342, DIN IEC 60095-2 |
| Application | Starter battery |
| Electrical data | |
| Rated voltage | 12V |
| Rated capacity | 30 Ah (K20) |
| Cold start current | 300 A (EN) |
| Dimensions and weights | |
| Box C11 |  |
| Length max. | |
| Width max. | |
| Box height max. | |
| Total height max. | |
| Battery weight | Ca. 8,0 kg (+/- 5 %) |
| Electrolyte density | Approx. 1,28 kg/l |
| Electrolyte | Diluted sulphuric acid |
| Items/pallet | 144 |
| Pallet ID | Euro palett |
| Items per layer | 36 |
| Features | |
| Base hold-down | B00 |
| Layout | 1 |
| Terminal | 4 |
| Separator | PE bag separator |
| Degassing | Battery with central degassing |
| Flame arrester | Not available |
| Maintenance ¹⁾ | |
| Water consumption | > 4g/Ah |
| Refill water | Distilled or demineralised (DIN 43530) |
| Self-discharge | Approx. 9 % per month |
| Charging current | Approx. 1/10 of the rated capacity |
| Charging voltage ²⁾ | max. 13,8 V |

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge

Document DBTBAT00293 prepared on 2013-09-19 ; Rights relating to changes and errors retained.
original